



Submittal Data Sheet

Daikin EMURA Silver 0.75 Ton Wall Mount Heat Pump System
FTXR09WVJUS9RX09WMVJU9

FEATURES

- Hot start technology
- Auto-restart (after power failure)
- IR controller included

BENEFITS

- Low ambient cooling operation down to -4°F (-20°C) with field setting and air adjustment grille
- Operating Range - Cooling (50°F - 114.8°F)
- Operating Range - Heating (5°F - 64.4°F)
- 12 Year limited parts and compressor warranty with online registration
- 5 year limited parts warranty for commercial applications

INDOOR UNIT



OUTDOOR UNIT





Submittal Data Sheet

Daikin EMURA Silver 0.75 Ton Wall Mount Heat Pump System
FTXR09WVJUS9RX09WMVJU9

SYSTEM PERFORMANCE

Indoor Unit Model No.	FTXR09WVJUS9	Indoor Unit Name:	Daikin EMURA 3/4 Ton Inv Wall mount Silver
Outdoor Unit Model No.	RX09WMVJU9	Outdoor Unit Name:	RX09WMVJU9
Rated Cooling Capacity (Btu/hr):	9,000	Rated Cooling Conditions:	Indoor (°F DB/WB): 80 / 67 Ambient (°F DB/WB): 95 / 75
Sensible Capacity (Btu/hr):		Rated Piping Length(ft):	25
Max/Min Cooling Capacity (Btu/hr):	10,600 / 4,500	Rated Height Difference (ft):	0.00
Cooling Input Power (kW):			
SEER2 (Non-Ducted/Ducted):	18.00 /	HSPF2 (Non-Ducted/Ducted):	7.5 /
EER2 (Non-Ducted/Ducted):	11.00 /	Heating COP (Non-Ducted/Ducted):	4.0 /
Rated Heating Capacity (Btu/hr):	10,000	Rated Heating Conditions:	Indoor (°F DB/WB): 70 / 60 Ambient (°F DB/WB): 47 / 43
Max/Min Heating Capacity (Btu/hr):	14,600 / 4,100		

SYSTEM DETAILS

Refrigerant Type:	R-410A	Cooling Operation Range (°F DB):	50 - 115
Holding Refrigerant Charge (lbs):	2.09	Heating Operation Range (°F WB):	5 - 64
Additional Charge (lb/ft):	0.21	Max. Pipe Length (Vertical) (ft):	49
Pre-charge Piping (Length) (ft):	33	Cooling Range w/Baffle (°F DB):	-4 - 115
Max. Pipe Length (Total) (ft):	66		
Max Height Separation (Ind to Ind ft):	0		

Submittal Data Sheet

Daikin EMURA Silver 0.75 Ton Wall Mount Heat Pump System


FTXR09WVJUS9RX09WMVJU9

INDOOR UNIT DETAILS

Power Supply (V/Hz/Ph):	208-230 / 60 / 1	Airflow Rate (H/M/L/SL) (CFM):	272/208/162/134
Power Supply Connections:	See Outdoor Unit for Electrical Specs	Moisture Removal (Gal/hr):	
Min. Circuit Amps MCA (A):		Gas Pipe Connection (inch):	3/8
Max Overcurrent Protection (MOP) (A):		Liquid Pipe Connection (inch):	1/4
Dimensions (HxWxD) (in):	11-15/16 x 39-5/16 x 8-3/8	Condensate Connection (inch):	11/16
Net Weight (lb):	27	Sound Pressure (H/M/L/SL) (dBA):	38/32/25/19
Ext. Static Pressure (Rated/Max) (inWg):	/	Sound Power Level (dBA):	

DIMENSIONAL DRAWING - INDOOR UNIT

FTXR09/12WVJUW(S)9



Submittal Data Sheet

Daikin EMURA Silver 0.75 Ton Wall Mount Heat Pump System


FTXR09WVJUS9RX09WMVJU9

OUTDOOR UNIT DETAILS

Power Supply (V/Hz/Ph):	208/230 / 60 / 1	Compressor Stage:	Inverter
Power Supply Connections:	1, 2, 3, Ground	Capacity Control Range (%):	-
Min. Circuit Amps MCA (A):	7.6	Airflow Rate (H) (CFM):	985
Max Overcurrent Protection (MOP) (A):	15	Gas Pipe Connection (inch):	3/8
Max Starting Current MSC(A):		Liquid Pipe Connection (inch):	1/4
Rated Load Amps RLA(A):	7.5	Sound Pressure (H) (dBA):	46
Dimensions (HxWxD) (in):	21-5/8 x 26-9/16 x 11-3/16	Sound Power Level (dBA):	
Net Weight (lb):	63		

DIMENSIONAL DRAWING - OUTDOOR UNIT

RX09/12WMVJU9





Submittal Data Sheet

Daikin EMURA Silver 0.75 Ton Wall Mount Heat Pump System
FTXR09WVJUS9RX09WMVJU9

INDOOR ACCESSORIES

PART NUMBER	DESCRIPTION	INCLUDED
AZAI6WSCDKB	DKN Residential Cloud Wi-Fi Adaptor for Single- and Multi-Zone System (S21)	No
AZAI6WSPDKC	DKN Plus Interface	No
BRC944B2-A08	Wired Remote Controller kit	No
BRCW901A03	BRC944B2 CONTROL CABLE, 10FT	No
BRCW901A08	Wired Remote Controller Cord - 8m/26ft	No
BRP072A43	Daikin Comfort Control WiFi Adaptor	No
DACA-CP1-1	Mini Aqua Condensate Pump	No
DACA-CP4-1	MINI WHITE PUMP KIT 100-250V	No
DCS301C71	Unified On/Off Controller	No
DCS302C71	Centralized Controller	No
DST301BA61	Schedule Timer	No
DTST-LTE-LA-A	Daikin One Lite (with Translation Adaptor for S21 only)	No
DTST-ONE-ADA-A	Daikin One+ Smart Thermostat for VRV, SkyAir, Single- and Multi-Zone System	No
KAF970A46	Titanium apatite photocatalytic air-purifying filter WITHOUT frame	No
KKF910A4	Loss Prevention Chain for Wireless Controller / Holder	No
KRP413AB1S	RA Adaptor PCB for Time Clock	No
KRP928BB2S	RA Interface Adaptor for DIII-Net -	No